





Architektur 53/135 lifting doors (easy-lift)

State: 11.11.2016




BRUNNER[®]
made in germany

Dimension sheet | **Architektur 53/135 lifting doors (easy-lift)**



We suggest for CAD planing Palette CAD. Permanent updated drawings: www.brunner.de
 Frames / front versions are marked colored.

Dimension sheet | **Architektur 53/135 lifting doors (easy-lift)**



Planning and installation

Architektur 53/135

Tested according to	EN 13229 W	EN 13229 W
Values measured at	rated heat power	open door
Suitable for all construction types according to rules	OK	OK
Data for functional demonstration		
Rated heat power	kW	14,5
Firewood consumption	kg/h	4,3
Combustion performance	kW	18
Flue gas mass flow	g/s	18
Outlet temperature (before heating surface)	°C	-
Flue gas temperature after		
attached steel smoke hood	°C	225
adjoining cast iron radiator (GNF10)	°C	-
accumulation rings (MAS) ¹⁾	°C	-
adjoining ceramic accumulator ²⁾	°C	-
accumulation stones (MSS)	°C	-
water boiler	°C	-
Necessary supply pressure	Pa	13
Combustion air consumption	m ³ /h	45
Combustion air connection Ø	mm	125
Heat distribution		
Insert / heating surface	%	60 / -
Glass (single / double)	%	40 / -
Boiler	%	-
Vent cross-section ⁴⁾		
Supply air	cm ²	900 / 100 / -
Warm air	cm ²	900 / 100 / -
Minimal oven surface for closed construction type		
Surface giving off heat	m ²	7,2
Space inside oven chamber		
Distance to oven chamber wall	cm	8
Distance to floor	cm	2
Heat insulation without / with ³⁾ air gratings		
Wall	cm	16 / 12
Floor	cm	4 / 2
Ceiling	cm	25 / 18
Insulation of additional fire door DHT	cm	-
Brick lining of protected walls	cm	10
Weight		
Fireplace + burning chamber	kg	329 + 125
meets requirement limit values for		
Germany / Austria / Switzerland / Norway	1.BImSchV (Stufe 2) / 15a BvG (2015) / LRV / NS 3059	

- 1) Throttle flap recommended
- 2) Approximate value, must be calculated eventually
- 3) Values with air gratings, stove casing is heat conducting
- 4) for firebox / flue gas pipe / metallic reheating surface

Ulrich Brunner GmbH
 Zellhuber Ring 17 -18
 D-84307 Eggenfelden
 Phone: +49 / (0)87 21 / 7 71-0
 Fax: +49 / (0)87 21 / 7 71-100
 info@brunner.eu | www.brunner.eu



BRUNNER products are offered and sold only by qualified dealers and service centres.
 Subject to technical and assortment changes. Errors excepted. (11/16)